

# LOBA Stain - the extremely fast stain for a strong color experience

Don't fancy long drying times? LOBA Stain is the quick-drying solution you've been looking for. With no unpleasant odours, your customers can use their room again in no time.

## Your advantages

- 1 hour drying time
- Safe and easy processing
- Ergonomic processing possible while standing
- Subsequent finishing with LOBA finishes or HardwaxOil
- · Odor dissipates quickly
- Not self-igniting

#### **COLOR VARIETY**

- All 12 color variants can be mixed with each other – for individual color design
- Flexible control of the color intensity by mixing the transparent variant with color variants



Art. Nr. 11525

**Available** in 750 ml, 12 colors and transparent. Also available as a sample.

Consumption approx. 45-60 ml/m<sup>2</sup>



Stain

# Range of use

For the professional coloring of wood floors. Compatible with LOBA primers and water-based finishes as well as with LOBA HardwaxOil.

# Colors and application



2x Hardwax0il







## **Application**

#### **PREPARE SUBSTRATE**

#### **APPLICATION LOBA STAIN**

OPTION 1

**With LOBA Microfiber Wiper:** a thin layer of LOBA Stain using a LOBA Microfiber Wiper, working in sections. Level with LOBASAND NormalPad white using a single-disc machine, remove excess.

OPTION 2

**Rag-on-Rag-off:** Apply LOBA Stain in sections with a lint-free cloth. Remove excess immediately with a second lint-free cloth.

#### DRYING

Wait for complete drying. Usually one hour. When building up with HardwaxOil, please wait 2 hours.

#### REFINEMENT

• **CONSTRUCTION A 3x LOBA finish\*:** Roll LOBA finish in three coats. Intermediate sanding is required before the final coat.

CONSTRUCTION B

**1x LOBA primer and 2x LOBA finish\*.** Intermediate sanding is required before applying the final coat.

CONSTRUCTION C

2x LOBA HardwaxOil with roller application.

# Microfiber wiper Art.-No. 16242



# Professional tips

# With brown and darker LOBA Stain colors, a more intense, richer color can be achieved if LOBA Amberizer is used in the primer and / or in the finish.

#### LOBA WHITENER

With lighter LOBA Stain colors, a more intense Scandinavian look can be achieved by using LOBA Whitener in the primer and/or in the finish.



#### SPECIAL CASE

#### White stain on oak and tannin-containing woods

• Apply LOBA Stain as described above and allow to dry.

#### **REFINING STRUCTURE**

• OPTION 1

Apply 2K InvisibleProtect twice. Intermediate sanding is required before the final coat.

- OPTION 2
- Stain drying time: 2 hours
- Apply PrimaSeal Plus 1x
- · 2 hours drying time
- Apply two coats of LOBA water-based finish.
   Intermediate sanding is required before the final coat.

### Cleaning & care

Even the most robust floor requires careful care to its beauty and functionality. Our care instructions will guide you and your customers from initial care to regular cleaning. Understanding and applying these steps correctly will keep the floor clean and preserve its quality and aesthetics.

- If the floor has been finished with LOBA HardwaxOil, please follow the cleaning and care instructions for oiled floors film forming.
- If the floor has been finished with LOBA water-based finishes, please follow the cleaning and care instructions for wood flooring finished with water-based finishes.



<sup>\*</sup> Please refer to the technical information, including the drying times of the respective products. Finishes that, according to the technical information, are already fully applied with two coats should also be applied accordingly in two coats using the Varnishing Rollers Deluxe 120.



Please refer to the detailed technical information, processing instructions and set-up recommendations.

LOBA GmbH & Co. KG Leonberger Str. 56–62 71254 Ditzingen | Deutschland Tel.: +49 7156 357-0 Fax: +49 7156 357-211 E-Mail: service@loba.de

www.loba.de



Find your LOBA contact:



® registered trademark at least in Germany